

Description	Value
Product name:	Unilift AP12.40.06.A1
Product No:	96001744
EAN number:	5700390472283
Technical:	
Max flow:	18 m ³ /h
Head max:	13 m
Type of impeller:	SEMI OPEN
Maximum particle size:	12 mm
Curve tolerance:	ISO 9906 Annex A
Materials:	
Material, pump housing:	Stainless steel 1.4301 DIN W.-Nr. 304 AISI
Material, impeller:	Stainless steel 1.4301 DIN W.-Nr. 304 AISI
Installation:	
Size, pump outlet:	Rp 1 1/2
Maximum installation depth:	10 m
Inst dry/wet:	D/S
Installation:	horizontal or vertical
Liquid:	
Liquid temperature range:	273 .. 328 K
Electrical data:	
Type of motor:	PSC
P1:	0.9 kW
P2:	0.6 kW
Mains frequency:	50 Hz
Rated voltage:	1 x 230 V
Rated current:	4.4 A
Cos phi - power factor:	0,99
Rated speed:	2785 rpm
Capacitor size - run:	16 µF/400 V
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Motor protec:	CONTACT
Thermal protec:	internal
Length of cable:	3 m
Type of cable plug:	AU
Controls:	
Level switch:	float switch A
Others:	
Net weight:	12 kg
Gross weight:	12.5 kg

