

Description	Value
Product name:	CHV 4-60
Product No:	44102106
EAN number:	5700393440449
Technical:	
Rated flow:	4 m ³ /h
Rated head:	39 m
Head max:	55 m
Type of shaft seal:	CVBE
Curve tolerance:	ISO 9906 Annex A
Pump version:	A
Model:	A
Materials:	
Material, pump housing:	Cast iron
Material, impeller:	Stainless steel
	1.4301 DIN W.-Nr.
	304 AISI
Material code:	A
Installation:	
Range of ambient temperature:	0 .. 55 °C
Max pressure at stated temp:	6 / 90 bar / °C
	10 / 40 bar / °C
Size, pump inlet:	Rp 1 1/4
Size, pump outlet:	Rp 1
Liquid:	
Liquid temperature range:	0 .. 90 °C
Electrical data:	
Power input (P1):	1450 W
P2:	1010 W
Mains frequency:	50 Hz
Rated voltage:	1 x 220-240 V
Rated current:	6.9 A
Starting current:	21 A
Capacitor size - run:	25 µF/400 V
Enclosure class (IEC 34-5):	IP54
Insulation class (IEC 85):	F
Motor protec:	CONTACT
Thermal protec:	internal
Others:	
Net weight:	16.5 kg
Gross weight:	17.6 kg
Shipping volume:	0.038 m ³

