

Description	Value
Product name:	CMB-SP 1-36 AVBE
Product No:	98507562
EAN number:	5711496303432
Price:	On request
Technical:	
Speed for pump data:	2900 rpm
Rated flow:	1.2 m³/h
Rated head:	29.7 m
Impellers:	4
Shaft seal:	AVBE
Approvals and markings:	CE,C-TICK
Curve tolerance:	ISO 9906:2012 Grade 3B
Model:	A
Self-priming:	4m
Materials:	
Pump housing:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Impeller:	Stainless steel DIN W.-Nr. 1.4301 AISI 304
Rubber:	EPDM
Installation:	
Maximum ambient temperature:	55 °C
Flange standard:	WHITWORTH THREAD RP
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	0 .. 60 °C
Liquid temp:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Maximum current consumption:	3,1-2,8 A
Rated power - P2:	0.5 kW
Mains frequency:	50 Hz
Rated voltage:	1 x 220-240 V
p max system:	10 bar
Enclosure class (IEC 34-5):	IP55
Insulation class (IEC 85):	F
Motor protec:	TP 211
Type of cable plug:	AU
Mains cable:	1.5 m
Others:	
Net weight:	14.1 kg
Gross weight:	22.2 kg

