

Suitable for Sprinkler Systems & Fire Fighting

- Compact & lightweight high pressure pump
- 3 ways delivery flange [2"x1, 1"x2]



SERH-50F SERM-50V



SERH-50F



Specifications

Model		SERH-50F	SERM50V
PUMP	Connection Dia.	Suction: 2" Delivery: 2" + 1" + 1"	
	Connection Thread	Mi BSP	
	Total Head	57 m (187 ft)	90m (295 ft)
	Delivery Volume	440 L/Min	500 L/Min
ENGINE	Max. Suction Head	8 M (26 ft)	
	Type	4-stroke, overhead valve, single-cylinder, horizontal shaft	
	Model	Honda GX160	Mitsubishi GM182 Hi-Rev
	Displacement:	163cc	181cc
	Rated Output	2.9kW (2.9PS) / 3600 rpm	3.3kW (4.5PS) / 3600 rpm
	Max. Output	3.6kW (4.9PS) / 3600 rpm	4.4kW (6.0PS) / 4800 rpm
	Fuel	Unleaded	
	Fuel Tank Capacity	3.1 L	3.5 L
	Continuous Operation Time	Approx. 2 Hours	
	Starter Method	Recoil Starter	
Standard Accessories		1 x Strainer	
		3 x Hose Clamps (60mm)	
		2 x Hose Bands (32mm)	
		1 x Coupling Set (50mm)	
		1 x Closing plate (50mm)	
		2 x Nipples (25mm)	
		1 x Quick Coupling	
		1 x Engine Tool	
Gross Weight		34 kg	38 kg
Dimensions LxWxH (mm)		535 x 405 x 440	555 x 450 x 468



SERM-50V



PUMPMASTER

AUSTRALIA